



Material Safety Data Sheet

According to Regulation (EU) No. 1907/2006 (REACH), Annex II (COMMISSION REGULATION (EU) No 453/2010)

Issue Date 06-Jan-2016

Revision date 06-Jan-2016

1. PRODUCT AND COMPANY IDENTIFICATION

Product name:	SIL-2 Gasket Maker (RTV silicone)
REACH registration number:	No information available
Product type:	Elastomeric rubber
Region:	UK
Company name:	FAI Automotive Plc.
Company address:	The Chiltern Trading Estate, Leighton Buzzard, Bedfordshire
Post code:	LU7 4TU
Phone:	0044 1525 351800
Fax:	0044 1525 351804
Email:	enquiry@faiauto.com
Website:	www.faiauto.com
Emergency:	0044 1525 351840

2. HAZARDS IDENTIFICATION

Toxicity: May cause eye and skin irritation. When this product is exposed to moisture, butanone oxime may be formed. May be harmful if swallowed. May irritate lips, gums, tongue, nose and mouth, throat.

Primary Routes of Entry: Eye and skin contact, ingestion, inhalation

Signs and Symptoms of Exposure: Butanone oxime produced during curing is toxic and irritates eyes, nose and throat. Overexposure to the silane may cause coma and respiratory failure.

Medical Conditions Recognized as Being Aggravated by Exposure: Preexisting eye, skin and respiratory disorders may be aggravated by overexposure to this product.

Label elements

Symbols/Pictograms:



Contains AMORPHOUS SILICA, DISTILLATES (PETROLEUM), HYDROTREATED MIDDLE Statements of hazard

H412 - Harmful to aquatic life with long lasting effects

Precautionary Statements - EU (§28, 1272/2008)

P273 - Avoid release to the environment

Other Information

- The classification as a carcinogen need not apply if the full refining history is known and it can be shown that the substance from which it is produced is not a carcinogen. This note applies only to certain complex oil derived substances in Annex I

- Acetic acid produced during curing can irritate eyes, nose and throat

3.COMPOSITION / INFORMATION ON INGREDIENTS

Component	Weight%	ACGIH; TLV-TWA	OSHA PEL
POLY (DIMETHYLSILOXANE), HYDROXY TERMINATED 70131-67-8	20-40	Not listed	Not listed
CALCIUM CARBONATE 471-34-1	20-30	10 mg/m ³	Not listed
LIMESTONE 1317-65-3	15-25	Not listed	15 mg/m ³
SYNTHETIC ISOPARAFFINIC HYDROCARBON 64742-47-8	5-15	Not listed	Not listed
VINYL OXIMINOSILANE 2224-33-1	<5	Not listed	Not listed
STEARIC ACID 57-11-	4<2	Not listed	Not listed
2-BUTANONE OXIME 96-29-7	0.5-2.0	Not listed	Not listed

4. FIRST AID MEASURES

Ingestion:	Rinse mouth. If swallowed, DO NOT induce vomiting. Keep individual calm. Obtain medical attention.
Inhalation:	Move to fresh air in case of accidental inhalation of vapours. If symptoms persist, call a physician.
Skin Contact:	Wipe off material with paper towel or cloth. Wash off with soap and water. If skin irritation persists, call a physician.
Eye Contact:	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

5. FIRE FIGHTING MEASURES

Flash Point °F(C°): >200°F TCC

Recommended Extinguishing Media: Carbon Dioxide, Dry Chemicals, Foam.

Special Fire-Fighting Procedures: Water spray may be ineffective on flames but should be used to keep fire exposed containers cool.

Hazardous Products of Combustion: Oxides of carbon, Oxides of nitrogen, Methyl ethyl ketone, possibly methyl ethyl ketoxime, Silica fume, Formaldehyde

Unusual Fire/Explosion Hazards: None.

Lower Explosive Limit: Not determined

Upper Explosive Limit: Not determined

6.ACCIDENTAL RELEASE MEASURES

Spill Procedures: Wipe or scrape up spill material. Maintain good ventilation for large spills. Place scrap material in a wellventilated area and allow to cure to rubber. Clean up spills thoroughly as residue is slippery.

7. HANDLING AND STORAGE

Storage: Keep containers tightly closed in a cool, well-ventilated place. Store away from water or moisture.

Handling: Avoid contact with skin and eyes. Do not wear contact lenses. Wash hands before eating and smoking.

Product may cause surfaces to become slippery.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eyes: Safety glasses.

Skin: Neoprene or nitrile gloves recommended.

Ventilation: General; local exhaust ventilation as necessary to control any air contaminants to within their exposure limits (or to the lowest feasible levels when limits have not been the established) during use of this product.

Respiratory Protection: An approved organic vapor respirator should be worn when exposures are expected to exceed the applicable limits.

Comments: When heated to temperatures above 300 degrees F. in the presence of air, this product can form formaldehyde vapors. Formaldehyde is a potential cancer hazard and a known skin and respiratory sensitizer. Safe handling conditions may be maintained by keeping vapor concentrations below the OSHA permissible limit for formaldehyde. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible materials. Gloves made from the following material(s) are recommended: luoroelastomer (Viton), Nitrile Rubber, Polyethylene/Ethylene Vinyl Alcohol.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Paste
Odor: Acetic
Boiling Point: Not applicable, polymeric material
pH: Does not apply
Solubility in Water: Polymerized
Specific Gravity: 0.95~1.05
VOC(Wt.%): <4%
Vapor Pressure: <5 mm Hg @ 80°F
Vapor Density (Air=1): 3.0
Evaporation Rate: Not Determined

10. STABILITY AND REACTIVITY

Chemical Stability: Stable at normal conditions

Hazardous Polymerization: Will not occur.

Incompatibilities: Polymerized by contact with moisture., Strong oxidizers, Acids, Iron

Conditions to Avoid: Exposure to moisture.

Hazardous Products of Combustion: Oxides of carbon, Oxides of nitrogen, Methyl ethyl ketone, possibly methyl ethyl ketoxime, Silica fume, Formaldehyde

11. TOXICOLOGICAL INFORMATION

See Section 3

12. ECOLOGICAL INFORMATION

No data available

13. DISPOSAL CONSIDERATIONS

Recommended Method of Disposal: Disposal should be made in accordance with federal, state and local regulations..

US EPA Waste Number: NH - Not a RCRA Hazardous Waste Material

14. TRANSPORT INFORMATION

Proper Shipping Name: Not regulated

Class or Division: None

UN/ID Number: None

IMDG

Proper Shipping: Not regulated

Hazard Class: None

UN Number: None

Marine Pollutant: None

15. REGULATORY INFORMATION

SARA 313 Chemicals: The following component(s) is listed as a SARA Section 313 Toxic Chemical. NONE

TSCA Inventory Status: All components of this product are listed (or exempt) on the EPA TSCA inventory.

16. OTHER INFORMATION

According to Regulation (EU) No. 1907/2006 (REACH), Annex II (COMMISSION REGULATION (EU) No 453/2010)

Issue Date: 06-Jan-2016

Revision date: 06-Jan-2016

Revision Note: Not applicable.

Estimated NFPA Rating: HEALTH 1, FLAMMABILITY 1, REACTIVITY 0.

Estimated HMIS Classification: HEALTH 1, FLAMMABILITY 1, PHYSICAL HAZARD 0

NFPA is a registered trademark of the National Fire Protection Assn.

HMIS is a registered trademark of the National Paint and Coatings Assn.

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, **FAI Automotive Plc** does not assume responsibility for any results obtained by persons over whose methods **FAI Automotive Plc** has no control. It is the user's responsibility to determine the suitability of **FAI Automotive Plc**'s products or any production methods mentioned herein for a particular purpose, and to adopt such

precautions as any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of **FAI Automotive Plc**'s products. In light of the foregoing, **FAI Automotive Plc** specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of **FAI Automotive Plc**'s products. **FAI Automotive Plc** further disclaims any liability for consequential or incidental damages of any kind, including lost profits.